



SARVASV
G R O U P

Extrusion Line

SARVASV offers a range of extrusion lines for PVC, PE, HDPE and XLPE Insulation and sheathing suitable for House Wire, Control Cable, Ariel Bunched Cables and Power Cable




www.sarvasv.com



Main features

- High linear outputs throughout a broad range of speed and pressure
- Robust construction
- Production flexibility over a large scope of application
- Special Screw Designs
- Highly efficient Extruder Gear Boxes
- Special Tooling and Cross Head arrangement for diverse needs
- Screw Cooling System
- Fully Automatic Control Panel with PID's and PLC Control for entire Line
- Accurate Diameter Control
- Range of Takeups and Payoffs available as per requirement
- Bi Color/ Tri Color Arrangements for dual/triple coating



Model	Max Speed (Rpm)	Kg /Hr. PVC / PE	Driven Motors (Kw)
SMPEL/EL/45	150	80 / 50	15
SMPEL/EL/65	120	150 / 90	30
SMPEL/EL/80	100	280 / 150	55
SMPEL/EL/100	80	375 / 225	75
SMPEL/EL/120	80	550 / 325	100
SMPEL/EL/150	60	700 / 425	200

Note : Since the Machines undergoes continues changes we reserve the right to modify the details
These Machine are Manufactured in Various Bobbin Size as Per DIN Stand.

EXTRUSION LINE



- OVERALL LENGTH OF MACHINE - 43 Meter
- OVERALL WIDTH OF MACHINE - 5 Meter



Regd. Office : A-153, Shivalik, New Delhi - 110 017, (India)
Corp. Office : B-200, Okhla Industrial Area, Phase-1, New Delhi-110020, (India)
Factory : B-195/194(B) Kahrani Ind. Area, Bhiwadi, Rajasthan-301019, (India)
Phone : +(91)-(11)-66401582, 66401583 Fax: +(91)-(11)-66401584
Mobile : +(91)-9871163831, 9810633630
Email : info@sarvasv.com, varun@sarvasv.com
Website : www.sarvasv.com